



UBT822

TILT DECK TRAILERS



INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

Unmatched 2-Year Bumper-to-Bumper Warranty on all components.
5-Year Structural Warranty.
Ask us for details.

Trailer details may differ from image

Loads Faster.

Brandt Work Ready™ tilt deck trailers deliver fast loading and unloading to maximize your output. The Lode N Lok™ auto-latching decks save you valuable time while increasing operator safety.

① Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn until the job gets done:

- A unified-frame design integrates the frame and deck into a single robust structure to minimize weak points and stress concentrations.
- Designed for optimal balancing with construction equipment, allowing for the most stable and secure load platform in the industry.
- Reliable design and long-lasting components reduce total cost of ownership.

② Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Lode N Lok™ self-locking deck enables faster loading, saving valuable time.
- Torsion spring suspension system delivers reliable shock-absorption without requiring any maintenance work.

③ Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Power Pin™ ball hitch is specially designed to automatically latch, ensuring that the trailer is properly secured to the towing vehicle, every single time.
- Foolproof locking mechanism automatically secures the deck once the equipment is loaded, maximizing safety.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.

Powerful Value. **Delivered.**

Brandt

TILT DECK TRAILERS SPECIFICATIONS

QUICK REFERENCE CHART	UBT822 Tandem Tilt		
Base Unit Key Specifications	PERFORMANCE	PREMIUM	PREMIUM GALVANIZED
RELIABILITY - RATED CAPACITY			
GVWR (lb)	16,000	16,500	
Rated Payload (lb)	12,400	12,700	12,600
Tongue Weight (lb)	2000		
Suspension	Torsion - Bolt On		
Axle Rating (lb)	2 x 7000	2 x 8000	
Maximum Weight on Fixed Deck (lb)	2000		
DURABILITY - STRUCTURE & FINISH			
HSS Mainframe Size (in)	8		
Premium Fir Decking	○	●	
Pressure-Treated Spruce/Pine Decking	○		
Polyurethane Primer & Paint	●	●	
Galvanized			●
DIMENSIONS			
Total Length (ft)	27.7		
Fixed Deck Length (ft)	6		
Tilt Deck Length (ft)	16		
Deck Width (in) – inside fender to fender	81.5	82.5	
Deck Height (in)	25		
INCLUDED EQUIPMENT			
Pull Type	Bumper		
Single Speed Jackleg Lift Capacity (lb)	10,000		
Hydraulic Cushion Cylinder	●		
Steel Tread Plate Fenders – bolt on	●		
Black Steel Wheels	●		
Tire Size	ST235/80R16 LRE	ST215/75R17.5LRH	
Premium Radial Tires – speed rated to 120 kph	10 ply	16 ply	
Aluminum Spoke Wheels	○		
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES			
4 x 4" D-Rings	●		
Premium Protected Wiring	●		
Breakaway Switch – includes LED test lights, battery & charger	●		
Integral Footholds	●		
Lode N Lok Deck	●		
Tier 1 LED Lighting System	●		
Forward Self-Adjusting Brakes	●		
E-Z Lube Oil Bath Axle Bearings	●		
E-Z Lube Grease Axle Bearings	●		
Deck Traction Aid – expanded steel mesh	○	●	
Heavy Duty Toolbox	○	●	
Tool Tray	○		
ADDITIONAL FEATURES			
Mud Flaps	○		
Pallet Fork Holders	○	●	
Spare Tire, Wheel, & Carrier	○	●	

AVAILABLE ACCESSORIES: Coupler Lock, Wheel Locks, and Tie Down Kit

● Included at no extra cost ○ Option available